Honeywell

Solstice® ZD, Solstice® 1233zd (E)

10628254			
Version 1.6		Revision Date 08/25/2021	Print Date 12/20/2023
SECTION 1. IDENTIFICATION			
Product name	:	Solstice® ZD, Solstice® 1233zd (E)	
Number	:	00000018007	
Product Use Description	:	Refrigerant, Heat transfer fluid	
Manufacturer or supplier's details For more information call	:	Honeywell International Inc. 115 Tabor Road Morris Plains, NJ 07950-2546 800-522-8001	
		+1-973-455-6300(Monday-Friday, 9:	00am-5:00pm)
In case of emergency call	:	Medical: 1-800-498-5701 or +1-303 Transportation (CHEMTREC): 1-80 527-3887	
	:	(24 hours/day, 7 days/week)	
SECTION 2. HAZARDS IDENTIF		ATION	
Emergency Overview			
Form		: liquid, clear	
Color		: colourless	
Odor		: slight	
Classification of the substa	anc	e or mixture	
Classification of the substance or mixture		: Gases under pressure, Liquefied gas Simple Asphyxiant	as
GHS Label elements, inclu	din	g precautionary statements	
		Page 1 / 14	

	ET		Honeywell
stice® ZD, Solsti	ce® 1233zd (E)		
528254 ion 1.6	Revision Date 08/25/202	21	Print Date 12/20/2
Symbol(s)			
Signal word	: Warning		
Hazard statements	: Contains gas under pres May displace oxygen an		
Precautionary statements	: Prevention: Use personal protective	equipment as r	equired.
	Storage: Protect from sunlight. St	ore in a well-ve	ntilated place.
	uct present at levels greater than only NTP, IARC, or OSHA.	or equal to 0.19	% is identified as a kno
No component of this prod or anticipated carcinogen I TION 3. COMPOSITION/I	DY NTP, IARC, or OSHA.		% is identified as a kno
No component of this prod or anticipated carcinogen I TION 3. COMPOSITION/I Chemical nature	by NTP, IARC, or OSHA. NFORMATION ON INGREDIENT : Substance	S	
No component of this prod or anticipated carcinogen I TION 3. COMPOSITION/I Chemical nature	by NTP, IARC, or OSHA. NFORMATION ON INGREDIENT : Substance al name C		% is identified as a kno Concentration >99.00 %
No component of this product or anticipated carcinogen I TION 3. COMPOSITION/I Chemical nature Chemic	by NTP, IARC, or OSHA. NFORMATION ON INGREDIENT : Substance al name Coropropene 102	S CAS-No.	Concentration
No component of this product of anticipated carcinogen I TION 3. COMPOSITION/I Chemical nature trans-1-Chloro-3,3,3-triflue	by NTP, IARC, or OSHA. NFORMATION ON INGREDIENT : Substance al name Coropropene 102	S CAS-No. 2687-65-0 breathing, give	Concentration >99.00 %
No component of this product of anticipated carcinogen in the second sec	NFORMATION ON INGREDIENT : Substance al name Coropropene 102 GURES : Remove to fresh air. If not If breathing is difficult, give	S CAS-No. 2687-65-0 breathing, give e oxygen. Use o tor is present. (sh immediately physician. Tak	Concentration >99.00 %
No component of this product of anticipated carcinogen in the second sec	NFORMATION ON INGREDIENT : Substance al name Coropropene 102 GURES : Remove to fresh air. If not If breathing is difficult, give provided a qualified opera : After contact with skin, wa If symptoms persist, call a clothing immediately. Was	S CAS-No. 2687-65-0 breathing, give e oxygen. Use o tor is present. (sh immediately physician. Tak	Concentration >99.00 %

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

628254		D	
sion 1.6		Revision Date 08/25/2021	Print Date 12/20/2
Eye contact	:	Rinse immediately with plenty of wate for at least 15 minutes. Call a physici persists.	
Ingestion	:	If victim is fully conscious, give a cup vomiting without medical advice. New to an unconscious person. Call a phy	ver give anything by mouth
Notes to physician			
Indication of immediate medical attention and special treatment needed, if necessary	:	Treat symptomatically.	
CTION 5. FIREFIGHTING MEA	SL	RES	
Suitable extinguishing media	:	The product is not flammable. Use extinguishing measures that are circumstances and the surrounding Water spray Carbon dioxide (CO2) Dry chemical Foam	
Specific hazards during firefighting	:	This product is not flammable at am atmospheric pressure. However, this material can ignite wh pressure and exposed to strong igni Container may rupture on heating. Cool closed containers exposed to f Do not allow run-off from fire fighting courses. Vapours are heavier than air and can reducing oxygen available for breath Exposure to decomposition products health. Fire may cause evolution of: Hydrogen fluoride Gaseous hydrogen chloride (HCI). Carbon oxides Halogenated compounds Carbonyl halides	tion sources. The with water spray. If the other drains or water an cause suffocation by hing.
		Page 3 / 14	

SAFETY DATA SHEET	Honeywell
olstice® ZD, Solstice@	रे 1233zd (E)
0628254	
ersion 1.6	Revision Date 08/25/2021 Print Date 12/20/202
Special protective equipment for firefighters	: In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit. No unprotected exposed skin areas.
ECTION 6. ACCIDENTAL RELE	ASE MEASURES
Personal precautions, protective equipment and emergency procedures	 Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Wear personal protective equipment. Unprotected persons must be kept away. Remove all sources of ignition. Ventilate the area. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Avoid accumulation of vapours in low areas. Unprotected personnel should not return until air has been tested and determined safe. Ensure that the oxygen content is >= 19.5%.
Environmental precautions	 Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers).
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
ECTION 7. HANDLING AND ST	ORAGE
Handling	
Precautions for safe handling	 Handle with care. Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Follow all standard safety precautions for handling and use of compressed gas cylinders. Use authorized cylinders only.
	Page 4 / 14

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

sion 1.6		Revision Date 08/25/2021	Print Date 12/20/20
		Protect cylinders from physical dam Do not puncture or drop cylinders, e or excessive heat. Do not pierce or burn, even after use flame or any incandescent material. Do not remove screw cap until imme Always replace cap after use.	e. Do not spray on a naked
Advice on protection against fire and explosion	:	Can form a combustible mixture with atmospheric pressure. Keep product and empty container a sources of ignition.	
Storage			
Conditions for safe storage, including any incompatibilities	:	Pressurized container. Protect from to temperatures exceeding 55 °C. Keep containers tightly closed in a c place. Storage rooms must be properly ver Ensure adequate ventilation, especi	ry, cool and well-ventilated
		Protect cylinders from physical dam Store away from incompatible subst	
CTION 8. EXPOSURE CONTI Protective measures	ROL :	Protect cylinders from physical dam	ances. afety showers are close to st.
	ROL :	Protect cylinders from physical dam Store away from incompatible subst S/PERSONAL PROTECTION Ensure that eyewash stations and s the workstation location. Do not breathe vapours or spray mis	ances. afety showers are close to st. othing.
Protective measures	ROL : :	Protect cylinders from physical dam Store away from incompatible subst S/PERSONAL PROTECTION Ensure that eyewash stations and s the workstation location. Do not breathe vapours or spray mis Avoid contact with skin, eyes and clu- Use with local exhaust ventilation. Perform filling operations only at sta	ances. afety showers are close to st. othing.
Protective measures Engineering measures	ROL : :	Protect cylinders from physical dam Store away from incompatible subst -S/PERSONAL PROTECTION Ensure that eyewash stations and s the workstation location. Do not breathe vapours or spray mis Avoid contact with skin, eyes and clo Use with local exhaust ventilation. Perform filling operations only at station ventilation facilities. Wear as appropriate: Safety glasses with side-shields	ances. afety showers are close to st. othing. tions with exhaust

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

10628254

Version 1.6	Revision Date 08/25/2021	Print Date 12/20/2023
Skin and body protection	: Wear as appropriate: Solvent-resistant gloves Solvent-resistant apron and boots If splashes are likely to occur, wear: Protective suit	
Respiratory protection	 In case of insufficient ventilation wear equipment. Wear a positive-pressure supplied-air For rescue and maintenance work in s contained breathing apparatus. Use NIOSH approved respiratory prot 	respirator. storage tanks use self-
Hygiene measures	 Handle in accordance with good industivative. Avoid contact with skin, eyes and cloth Do not breathe vapours or spray mist. Ensure adequate ventilation, especial Remove and wash contaminated cloth Contaminated work clothing should not workplace. Keep working clothes separately. Wash hands before breaks and imme product. 	hing. ly in confined areas. hing before re-use. ot be allowed out of the
Exposure Guidelines		

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Upda te	Basis
trans-1-Chloro- 3,3,3- trifluoropropene	102687-65-0	TWA : Time weighted average	(800 ppm)	2014	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide, as amended

3,3,3- trifluoropropene	TWA : (800 p Time weighted average	ppm) 2013	Honeywell:Limit established by Honeywell International Inc.
----------------------------	---	-----------	--

Page 6 / 14

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

10628254

Version 1.6

Revision Date 08/25/2021

Print Date 12/20/2023

Physical state	: liquid, clear	
Color	: colourless	
Odor	: slight	
Melting point/range	: < -90 °C Method: OECD Test Guideline 102	
Boiling point/boiling range	: 19 °C Method: OECD Test Guideline 103	
Flash point	: Method: ISO 2719 Note: Not applicable	
Evaporation rate	: Note: No data available	
Flammability	: The product is not flammable. Method: Flammability (gases)	
Lower explosion limit	: Note: None	
Upper explosion limit	: Note: None	
Vapor pressure	: 1,516 hPa at 30 °C(86 °F)	
Vapor density	: Note: (Air = 1.0), not determined	
Density	: 1.27 g/cm3	
Water solubility	: 1.90 g/l at 20 °C	
	Method: OECD Test Guideline 105	
	Page 7 / 14	

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

10628254

ersion 1.6	Revision Date 08/25/2021	Print Date 12/20/20
Dertition coefficients n		
Partition coefficient: n- octanol/water	: log Pow: 2.2 at 25 °C	
Ignition temperature	: 380 °C at 986.8 - 1,035.9 hPa Method: DIN 51794	
Decomposition temperature	: > 250 °C	
Viscosity, dynamic	: Note: No data available	
Viscosity, kinematic	: Note: No data available	
Oxidizing properties	: The substance or mixture is not classif	ied as oxidizing.
Molecular weight	: 130.5 g/mol	

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Polymerisation can occur.
Conditions to avoid	 Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 55 °C. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
Incompatible materials	: Strong oxidizing agents Finely divided magnesium Finely divided aluminium
Hazardous decomposition products	 Halogenated compounds Carbon oxides Hydrogen fluoride Carbonyl halides Gaseous hydrogen chloride (HCI).
	Page 8 / 14

In mala m A. C		
Version 1.6	Revision Date 08/25/2021	Print Date 12/20/2
SECTION 11. TOXICOLOGICAL	INFORMATION	
Acute inhalation toxicity	: LC50: 120000 ppm Exposure time: 4 h Species: Rat	
Skin irritation	: Species: Rabbit Result: No skin irritation Classification: Not classified as a skin Method: OECD Test Guideline 404 Exposure time: 4 h	irritant in animal testing.
Sensitisation	: Result: Does not cause skin sensitisat Classification: Patch test on human vo demonstrate sensitisation properties.	
Repeated dose toxicity	: Species: Rat Application Route: Inhalation Exposure time: 4 Weeks NOEL: 4500 ppm Note: Subacute toxicity	
Genotoxicity in vitro	: Test Method: Mutagenicity (Salmonell mutation assay) Metabolic activation: with and without Result: negative	
	 Test Method: Mutagenicity (Escherich assay) Metabolic activation: with and without Result: negative Method: OECD Test Guideline 471 	
	: Test Method: Chromosome aberration Cell type: Human lymphocytes Result: negative	a test in vitro

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

628254		B I I B I B I B I B I B I B I B I B I B I B I B I B B I B B I B B B B B B B B B B
sion 1.6	Revision Date 08/25/2021	Print Date 12/20/2
	Method: OECD Test Guideline 473	3
Genotoxicity in vivo	: Species: Rat Cell type: Bone marrow	
	Method: Mutagenicity (micronucle Result: negative	us test)
Genotoxicity in vivo	: Test Method: Unscheduled DNA s Species: Rat	ynthesis
	Result: negative	
Genotoxicity in vivo	: Species: Mouse Cell type: Bone marrow	
	Method: Mutagenicity (micronucle Result: negative	us test)
Reproductive toxicity	: Species: Rabbit Note: No-observed-effect level - 1	5.000 mag
	: Species: Rat	
	Note: No-observed-effect level - 10	0,000 ppm
Teratogenicity	: Species: Rabbit Note: No-observed-effect level - 1	5,000 ppm
	: Species: Rat	
	Note: No-observed-effect level - 10	0,000 ppm
Further information	: Note: Excessive exposure may car effects including drowsiness and d Sensitization (dog): No observed 100000 ppm.	lizziness. Cardiac
TION 12. ECOLOGICAL I	NFORMATION	
Ecotoxicity effects		
Toxicity to fish	: LC50: 38 mg/l	
	Page 10 / 14	

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

0628254		
rsion 1.6	Revision Date 08/25/2021	Print Date 12/20/202
	Exposure time: 96 h Species: Oncorhynchus mykiss (rai Method: OECD Test Guideline 203	inbow trout)
Toxicity to daphnia and other aquatic invertebrates	: Immobilization EC50: 82 mg/l Exposure time: 48 h Species: Daphnia magna (Water fle Method: OECD Test Guideline 202	
Toxicity to algae	 Growth inhibition EC50: > 215 mg/l Exposure time: 72 h Species: Pseudokirchneriella subca Method: OECD Test Guideline 201 Growth rate NOEC: 115 mg/l Exposure time: 72 h Species: Pseudokirchneriella subca Method: OECD Test Guideline 201 	
Elimination information (per	sistence and degradability)	
Bioaccumulation	: Note: Due to the distribution coeffic accumulation in organisms is not ex	
Biodegradability	: Result: Not readily biodegradable. Value: 0 % Method: OECD 301 D	
Further information on ecol	ogy	
Ecotoxicology Assessment		
	red to be very persistent and very bioact b be persistent, bioaccumulating and tox	
CTION 13. DISPOSAL CONSI	DERATIONS	
	Page 11 / 14	
	Faye II / 14	

0628254 ersion 1.6		sion Date 08/25/2021	Print Date 12/20/202
		ve all Federal, State, and Loca	
Note	: Wher	e possible recycling is preferred eration.	d to disposal or
ECTION 14. DOT	TRANSPORT INFORMATION UN/ID No. Proper shipping name Class Packing group Hazard Labels	: UN 3163 : LIQUEFIED GAS, N.O.S. (Trans-1-Chloro-3,3,3-trifle 2.2 2.2	uoropropene)
ΙΑΤΑ	UN/ID No. Description of the goods Class Hazard Labels Packing instruction (cargo aircraft) Packing instruction (passenger aircraft)	 : UN 3163 : LIQUEFIED GAS, N.O.S. (Trans-1-Chloro-3,3,3-trifle) : 2.2 : 2.2 : 200 : 200 	uoropropene)
IMDG	UN/ID No. Description of the goods Class Hazard Labels EmS Number Marine pollutant	 UN 3163 LIQUEFIED GAS, N.O.S. (TRANS-1-CHLORO-3,3, TRIFLUOROPROPENE) 2.2 2.2 F-C, S-V no 	3-
Inventor	c Substances : On TSC	N CA Inventory	

Honeywell

Solstice® ZD, Solstice® 1233zd (E)

628254		Devision Data 00/05/0004	Drint Data 10/00/00
sion 1.6		Revision Date 08/25/2021	Print Date 12/20/20
Australia. Industrial Chemical (Notification and Assessment) Act	:	On the inventory, or in compliance wit	th the inventory
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)	:	All components of this product are on	the Canadian DSL
Japan. Kashin-Hou Law List	:	On the inventory, or in compliance wit	th the inventory
Korea. Existing Chemicals Inventory (KECI)	:	On the inventory, or in compliance wit	th the inventory
Philippines. Inventory of Chemicals and Chemical Substances (PICCS)	:	Not in compliance with the inventory	
	:		102687-65-0
China. Inventory of Existing		trifluoropropene On the inventory, or in compliance wit	th the inventory
Chemical Substances (IECSC)	•	on the inventory, of in compliance with	
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	:	On the inventory, or in compliance wit	th the inventory
National regulatory informa	atio	n	
SARA 302 Components	:	No chemicals in this material are subj requirements of SARA Title III, Sectio	
SARA 313 Components	:	This material does not contain any ch known CAS numbers that exceed the reporting levels established by SARA	threshold (De Minimis)
SARA 311/312 Hazards	:	Acute Health Hazard Sudden Release of Pressure Hazard	

AFETY DATA SHEE	Г	Honeywell
olstice® ZD, Solstice	e® 1233zd (E)	
0628254		
rsion 1.6	Revision Date 08/25/20	021 Print Date 12/20/202
California Prop. 65		ntain any chemicals known to State of r, birth defects, or any other
New Jersey RTK	: trans-1-Chloro-3,3,3- trifluoropropene	102687-65- 0
Pennsylvania RTK	: trans-1-Chloro-3,3,3- trifluoropropene	102687-65- 0
Health hazard Flammability	HMIS III NFPA : 2 2 : 0 0	
Flammability Physical Hazard Instability Hazard rating and rating sys	: 2 2 : 0 0 : 0 : 0 : 0 stems (e.g. HMIS® III, NFPA):	This information is intended solely for the
Flammability Physical Hazard Instability	: 2 2 : 0 0 : 0 : 0 : 0 stems (e.g. HMIS® III, NFPA):	This information is intended solely for the
Flammability Physical Hazard Instability Hazard rating and rating sys use of individuals trained in Further information The information provided in information and belief at the guidance for safe handling, to be considered a warranty material designated and ma materials or in any process,	 2 2 2 0 0 2 0 3 3 4 4 4 5 4 4<	This information is intended solely for the ect to the best of our knowledge, ormation given is designed only as a sportation, disposal and release and is no formation relates only to the specific I used in combination with any other nal determination of suitability of any ion should not constitute a guarantee for
 Flammability Physical Hazard Instability Hazard rating and rating systems of individuals trained in Further information The information provided in information and belief at the guidance for safe handling, to be considered a warranty material designated and ma materials or in any process, material is the sole responsiany specific product propert Changes since the last versions. Previous Issue Date: 08/25/ 	 2 2 2 0 0 2 0 3 3 4 4<	ect to the best of our knowledge, ormation given is designed only as a sportation, disposal and release and is no formation relates only to the specific I used in combination with any other nal determination of suitability of any